

100% Asbestos Free

# HANOVER® RC TACK PRIMER

Asphalt cutback used to develop adhesion between old and new pavement

VOC Content < 225 g/l

## Description

A highly versatile asphalt cutback designed to develop adhesion between old pavement and the subsequent surface course. RC Tack meets or exceeds all requirements set forth by ASTM D 2028.

## Uses

This material is an asphalt cutback formulated to be a premium coating used for penetration, priming and binding of bituminous surfaces during resurfacing or patching.

## Coverage

150 - 250 square feet per gallon

## Net Contents

5 US Gallons ( 18.925 L)

## Application

Consists of a very light application of bituminous asphalt on an existing surface  
For complete application instructions, refer to product label.

Before using this product, read the Material Safety Data Sheet for additional safety precautions.  
To request a Material Safety Data Sheet, call 800.426.4242 or visit [www.hanoverpavers.com](http://www.hanoverpavers.com).

## Cautions

COMBUSTIBLE! DO NOT use or store near flames, sparks or heat. DANGER, harmful or fatal if swallowed. Harmful to eyes and skin. DO NOT get in eyes, on skin, or in clothing. Wear goggles, gloves and protective clothing when handling product. DO NOT breathe vapors or fumes. Use only with adequate ventilation, equivalent to outdoors. Use with explosion proof equipment. Keep out of sewers and water courses and advise authorities if unable to do so.

**HANOVER®**  
**Architectural Products**  
5000 Hanover Road, Hanover, PA 17331  
717.637.0500 • fax 717.637.7145  
[www.hanoverpavers.com](http://www.hanoverpavers.com)