

100% ASBESTOS FREE

Paver Mastic

Product Information

used for adhering
brick or block in
paving applications

VOC Content < 150 g/l

2% Neoprene Modified

Description:

Paver Mastic is a high quality modified asphalt mastic designed expressly as an adhesive for bricks and pavers.

Coverage:

30 - 50 square feet per gallon (150 - 250 square feet per pail)

Net Contents:

5 US Gallons (18.925 L)

Application:

Paver Mastic must be applied to surface free of all foreign matter. Paver Mastic should be applied as a skim coat to a 1/16" maximum with a straight edge trowel or squeegee. Allow mastic to flash off but not dry before embedding pavers. For best results, the temperature is recommended to be above 70°F. Paver Mastic should yield a coverage rate of 30 - 50 sq. ft. per gallon. This material may bleed or seep through the block if the mastic is applied to heavily.

Cautions:

COMBUSTIBLE! DO NOT use or store near flames, sparks or heat. Harmful to eyes and skin. DO NOT get in eyes, on skin, or in clothing. Wear goggles, gloves and protective clothing when handling product. DO NOT breathe vapors or fumes. For outdoor use only. Keep out of sewers and water courses and advise authorities if unable to do so.

Before using this product, read the Material Safety Data Sheet for additional safety precautions.
To request a Material Safety Data Sheet, call 800.426.4242 or visit www.hanoverpavers.com.

HANOVER[®]
Architectural Products
240 Bender Road, Hanover, PA 17331
717.637.0500 • fax 717.637.7145
www.hanoverpavers.com