

SUREBOND®

PAVER BOND®

SB-10



USES

Retaining Walls and concrete, clay and natural stone paving.

OTHER USES*

Natural and manufactured stone, brick, concrete, terrazzo and hard clay tiles in horizontal and vertical applications. Also adheres to other building materials such as treated lumber, aluminum foil back sheathing, gypsum, fiberglass and other rigid decking materials.

*SUPPLEMENTARY INFORMATION AVAILABLE

RELATED PRODUCTS

Joint Stabilizing Sealer® SB-1300, Bright Protector® Cleaner SB-442, Bright Protector® Efflorescence & Rust Remover SB-488

PRODUCT DESCRIPTION

Paver Bond® SB-10 is a high strength, high quality structural grade construction adhesive. Paver Bond is a freeze thaw resistant all weather adhesive. Perfect for retaining wall capping and other outdoor and indoor applications. It is durable enough to withstand extreme wear and tear including heavy vehicular traffic. It is easy to apply with a good consistency that naturally shims, levels and sets in 20 minutes. Paver Bond is a quick curing adhesive for a long-lasting professional installation. It has good coverage, is reliable and easy to apply making it economical to use.

APPLICABLE STANDARDS

- UN-STD. 1804
- ASTM 2339-70
- FHA UM-60

FEATURES	BENEFITS
What makes Paver Bond unique?	
<i>Premium Product</i>	• Manufacturers most widely recommended
<i>5 X Stronger</i>	• Withstands extreme wear and tear
<i>Easy to Apply</i>	• Naturally shims and levels
<i>Quick Setting</i>	• Sets in 20 minutes
<i>Water and Weather resistant</i>	• Withstands winter freeze-thaw conditions
<i>Durable</i>	• Withstands even heavy vehicular traffic
<i>Heat Resistant</i>	• Does not slip in hot, humid weather
<i>Versatile</i>	• Used with most construction materials

PREPARATION

Inspect the substrate to ensure that it is structurally sound. For older concrete clean with SB 442 Bright Protector® Cleaner. Layout design should be done before installation begins. The surface of the pavers should be clean, dry and free of dust or dirt for proper bonding. Before applying adhesive inspect pavers or stone to insure they are smooth, flat, and of the same height. Set pavers so they lay flat and level. Ensure proper drainage so water does not collect or drain into undesired areas.

APPLICATION INFORMATION

Cut the cartridge tips to produce a 3/8" inch bead and puncture the seal. Apply a 1/4" to 3/8" bead of Paver Bond Adhesive to pavers or stone to form an "S" shape in the center of the bonding surface and around the bonding surface's edges at least 1/2" from the edge. Set the stone in place and stamp the stone down gently with a rubber mallet to compress the adhesive.

APPLICATION EQUIPMENT SUGGESTIONS

10.3 oz. caulking gun

PACKAGING/SIZES

24 x 10.3 oz. cartridges per case
5 gallon pail

COVERAGE

10.3 oz. cartridge	1/8" bead	123 linear feet
10.3 oz. cartridge	1/4" bead	30 linear feet

Actual coverage may vary depending on the type, age, condition and application method. These coverage rates are, to our best knowledge, accurate and true.

OTHER USES COVERAGE*

10.3 oz. cartridge	1/8" bead	123 linear feet
10.3 oz. cartridge	1/4" bead	30 linear feet

Actual coverage may vary depending on the type, age, condition and application method. These coverage rates are, to our best knowledge, accurate and true. * - SUPPLEMENTARY INFORMATION AVAILABLE

DRYING TIME

Adhesive starts to set within twenty minutes and should be in place within 10 to 15 minutes. Full strength cure takes at least 7 days.

STORAGE

Store cartridges in upright position in a cool place, rotate stock, keep at 70°F for 24 hours before use in cold weather.

SUREBOND®

PAVER BOND®

SB-10

SHELF LIFE

Paver Bond has a shelf life of 1 year.

LIMITATIONS

Test application is always recommended to ensure both the proper physical and aesthetic properties prior to starting a project. Keep at 70°F for 24 hours before use in cold weather. Keep out of reach of children. EXTREMELY FLAMMABLE AND TOXIC (see CAUTION on label).

WARRANTY

Manufacturer warrants its products conform to the published specifications. No other warranties are expressed or implied, including those of merchantability or fitness for any purpose not expressly set forth herein. The user must determine suitability of the products for their particular use. Manufacturer and any seller's liability for incidental or consequential damage hereunder shall not exceed the purchase price of the product used.

FOR ASSISTANCE & ADDITIONAL INFORMATION

This is recommended prior to specification. Consult Surebond International for specification assistance, detailing etc. We offer sales support through our Sales Representatives located throughout the country.

SUREBOND INTERNATIONAL
P.O. Box 17147, Irvine, CA 92614
(866) 600-SURE or (949)797-9000
www.surebond.com

DISTRIBUTED BY:
HANOVER ARCHITECTURAL PRODUCTS
240 BENDER ROAD
HANOVER, PA 17331
(717) 837-0500