

TECHNICAL DATA SHEET

DIRT AND GREASE CLEANER FOR PAVERS AND SLABS

UPDATE

September 27, 2002

Make sure that you have an up-to-date technical data sheet at hand.
Canada and U.S.A.: dial 1-800-465-7325.
Others: dial 514-523-8324 (Canada).

FUNCTION

Dissolves, dislodges and encapsulates grease.

APPLICATIONS

- Sealed or bare surfaces.
- Pavers and slabs made of concrete or natural stone, masonry, etc.
- Concrete, clay, stone, marble, granite, slate, etc.
- Driveways, pool decks, patios, terraces, commercial parking lots, pedestrian areas, buildings, etc.

DESCRIPTION

TECHNI-SEAL DIRT AND GREASE CLEANER is the most effective product available for removing motor oil and grease (barbecue) stains from concrete or natural stone pavers and slabs. It dissolves, dislodges and encapsulates grease, thoroughly cleaning without leaving any oily film after rinsing.

DIRECTIONS

Read the Material Safety Data Sheet before using this product. Wear adequate protective clothing. On a sealed surface, wet the stain before applying product; on a bare surface, apply dry. Cover the stain generously with DIRT AND GREASE CLEANER; let work for 2 to 3 minutes; reapply product and scrub with a SMALL TECHNI-SEAL BRUSH; do not let product dry on the surface; rinse thoroughly. Repeat if necessary.

NOTE

An oil spot that has penetrated the material may resurface within 24 hours following cleaning; if the case arises, repeat the process. An oil stain on a light-coloured surface may leave a blackish mark after cleaning; lighten the mark using REMOVER (141-541/241-547) or EFFLORESCENCE CLEANER (141-534/241-537).

PACKAGING

| Product Code | Retail Size | Pro Size | Units per box | Units per pallet |
|--------------|-------------|----------|---------------|------------------|
| 141-512 | 2 L | • | 6 | 216 |
| 241-517 | • | 20 L | • | 48 |

2 L = 2 U.S. qt.
20 L = 5.28 U.S. gal.

SHIPPING**Land and Sea**

Not regulated

LIMITED WARRANTY: Since it has no control over surface preparation and product application, Techni-Seal can not guarantee the results. Techni-Seal's warranty is limited to the replacement or reimbursement of product proven defective. Note: User should have an up-to-date technical data sheet handy and make sure that this product meets his or her needs by carrying out a test under anticipated conditions of use.