

HANOVER® NATURAL SEALER

For Paver and Sand Joints



- Enhances appearance and color
- Protects against oil and dirt penetration on paver surface
- Makes surface easy to clean
- Reinforces joints by keeping sand in place
- Minimizes erosion and weed growth
- Environmentally compliant

A PROTECTING SEALANT THAT ALLOWS BREATHABILITY OF THE CONCRETE MASONRY OR PAVER UNIT

Hanover® Natural Sealer enhances the appearance of the architectural concrete masonry units. It is impervious to liquids, yet is vapor/air permeable. Natural Sealer forms a long lasting protection barrier from water, dirt, oil and UV light while allowing the paver surface to breathe. Pavers maintain a natural appearance while color is softly enhanced.

Hanover® Pavers are designed to be a low maintenance investment. However, pavers may be sealed for preservation or color enhancement. Hanover® suggests a complete paver cleaning prior to sealing. Major stains must first be removed with specialized cleaner designed for the type of stain, followed by a cleaning of the entire area with a general cleaner. It is best to seal pavers soon after they have been thoroughly cleaned. Pavers and joints must be completely dry, clean and free of oil, grease, dust, dirt, sand, efflorescence and frost. It is advised that sealers not be applied when temperatures are below 50°F. Hanover® Sealers provide excellent protection from water, alkalis, acids, air borne pollutants and ultraviolet light, making pavers easier to clean.

COVERAGE

Rough Surface = 150 sq ft/gal @ 1.0 mil
Smooth Surface = 200 sq ft/gal @ 1.0 mil
Consumption will depend on surface porosity.

NET CONTENTS

1 US Gallon (3.7853 L) or 5 US Gallon (18.9 L)
Weight/Gallon: 8.52 lb/gal

APPLICATION

Natural Sealer is ready to use and requires no mixing or dilution. Surface must be clean, dry, free from oil, grease, dust, dirt, sand, efflorescence and frost. Natural Sealer is sprayable with an airless metal sprayer or can be applied with a brush or roller. Apply over clean, dry block. Exterior applications only. Sealer may increase slipperiness. Do not apply Sealer too heavily. Over application can create a milky fog on the paver surface. For complete application instructions, refer to product label.

Before using this product, read the Material Safety Data Sheet for additional safety precautions. To request a Material Safety Data Sheet, call 800.426.4242 or visit www.hanoverpavers.com.

HANOVER®
Architectural Products
5000 Hanover Road, Hanover, PA 17331
717.637.0500 • fax 717.637.7145
www.hanoverpavers.com